

## NAG Library Function Document

### nag\_dorglq (f08ajc)

## 1 Purpose

nag\_dorglq (f08ajc) generates all or part of the real orthogonal matrix  $Q$  from an  $LQ$  factorization computed by nag\_dgelqf (f08ahc).

## 2 Specification

```
#include <nag.h>
#include <nagf08.h>
void nag_dorglq (Nag_OrderType order, Integer m, Integer n, Integer k,
                 double a[], Integer pda, const double tau[], NagError *fail)
```

## 3 Description

nag\_dorglq (f08ajc) is intended to be used after a call to nag\_dgelqf (f08ahc), which performs an  $LQ$  factorization of a real matrix  $A$ . The orthogonal matrix  $Q$  is represented as a product of elementary reflectors.

This function may be used to generate  $Q$  explicitly as a square matrix, or to form only its leading rows. Usually  $Q$  is determined from the  $LQ$  factorization of a  $p$  by  $n$  matrix  $A$  with  $p \leq n$ . The whole of  $Q$  may be computed by:

```
nag_dorglq(order,n,n,p,&a,pda,tau,&fail)
```

(note that the array **a** must have at least  $n$  rows) or its leading  $p$  rows by:

```
nag_dorglq(order,p,n,p,&a,pda,tau,&fail)
```

The rows of  $Q$  returned by the last call form an orthonormal basis for the space spanned by the rows of  $A$ ; thus nag\_dgelqf (f08ahc) followed by nag\_dorglq (f08ajc) can be used to orthogonalize the rows of  $A$ .

The information returned by the  $LQ$  factorization functions also yields the  $LQ$  factorization of the leading  $k$  rows of  $A$ , where  $k < p$ . The orthogonal matrix arising from this factorization can be computed by:

```
nag_dorglq(order,n,n,k,&a,pda,tau,&fail)
```

or its leading  $k$  rows by:

```
nag_dorglq(order,k,n,k,&a,pda,tau,&fail)
```

## 4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

## 5 Arguments

1: **order** – Nag\_OrderType *Input*

*On entry:* the **order** argument specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = Nag\_RowMajor. See Section 3.2.1.3 in the Essential Introduction for a more detailed explanation of the use of this argument.

*Constraint:* **order** = Nag\_RowMajor or Nag\_ColMajor.

|   |  |                     |
|---|--|---------------------|
| 2:  | <b>m</b> – Integer                       | <i>Input</i>        |
| <i>On entry:</i> $m$ , the number of rows of the matrix $Q$ .   |  |                     |
| <i>Constraint:</i> $\mathbf{m} \geq 0$ .  |  |                     |
| 3:  | <b>n</b> – Integer                       | <i>Input</i>        |
| <i>On entry:</i> $n$ , the number of columns of the matrix $Q$ .  |  |                     |
| <i>Constraint:</i> $\mathbf{n} \geq \mathbf{m}$ .   |  |                     |
| 4:  | <b>k</b> – Integer                       | <i>Input</i>        |
| <i>On entry:</i> $k$ , the number of elementary reflectors whose product defines the matrix $Q$ .   |  |                     |
| <i>Constraint:</i> $\mathbf{m} \geq \mathbf{k} \geq 0$ .  |  |                     |
| 5:  | <b>a</b> [ <i>dim</i> ] – double         | <i>Input/Output</i> |
| <b>Note:</b> the dimension, <i>dim</i> , of the array <b>a</b> must be at least   |  |                     |
| max(1, <b>pda</b> × <b>n</b> ) when <b>order</b> = Nag_ColMajor;  |  |                     |
| max(1, <b>m</b> × <b>pda</b> ) when <b>order</b> = Nag_RowMajor.  |  |                     |
| <i>On entry:</i> details of the vectors which define the elementary reflectors, as returned by nag_dgelqf (f08ahc).                         |  |                     |
| <i>On exit:</i> the $m$ by $n$ matrix $Q$ .   |  |                     |
| If <b>order</b> = 'Nag_ColMajor', the $(i,j)$ th element of the matrix is stored in <b>a</b> [( <i>j</i> − 1) × <b>pda</b> + <i>i</i> − 1]. |  |                     |
| If <b>order</b> = 'Nag_RowMajor', the $(i,j)$ th element of the matrix is stored in <b>a</b> [( <i>i</i> − 1) × <b>pda</b> + <i>j</i> − 1]. |  |                     |
| 6:  | <b>pda</b> – Integer                     | <i>Input</i>        |
| <i>On entry:</i> the stride separating row or column elements (depending on the value of <b>order</b> ) in the array <b>a</b> .             |  |                     |
| <i>Constraints:</i>   |  |                     |
| if <b>order</b> = Nag_ColMajor, <b>pda</b> $\geq$ max(1, <b>m</b> );  |  |                     |
| if <b>order</b> = Nag_RowMajor, <b>pda</b> $\geq$ max(1, <b>n</b> ).  |  |                     |
| 7:  | <b>tau</b> [ <i>dim</i> ] – const double | <i>Input</i>        |
| <b>Note:</b> the dimension, <i>dim</i> , of the array <b>tau</b> must be at least max(1, <b>k</b> ).  |  |                     |
| <i>On entry:</i> further details of the elementary reflectors, as returned by nag_dgelqf (f08ahc).  |  |                     |
| 8:  | <b>fail</b> – NagError *                 | <i>Input/Output</i> |
| The NAG error argument (see Section 3.6 in the Essential Introduction).   |  |                     |

## 6 Error Indicators and Warnings

### NE\_ALLOC\_FAIL

Dynamic memory allocation failed.

### NE\_BAD\_PARAM

On entry, argument  $\langle\text{value}\rangle$  had an illegal value.

**NE\_INT**

On entry,  $\mathbf{m} = \langle \text{value} \rangle$ .

Constraint:  $\mathbf{m} \geq 0$ .

On entry,  $\mathbf{pda} = \langle \text{value} \rangle$ .

Constraint:  $\mathbf{pda} > 0$ .

**NE\_INT\_2**

On entry,  $\mathbf{m} = \langle \text{value} \rangle$  and  $\mathbf{k} = \langle \text{value} \rangle$ .

Constraint:  $\mathbf{m} \geq \mathbf{k} \geq 0$ .

On entry,  $\mathbf{n} = \langle \text{value} \rangle$  and  $\mathbf{m} = \langle \text{value} \rangle$ .

Constraint:  $\mathbf{n} \geq \mathbf{m}$ .

On entry,  $\mathbf{pda} = \langle \text{value} \rangle$  and  $\mathbf{m} = \langle \text{value} \rangle$ .

Constraint:  $\mathbf{pda} \geq \max(1, \mathbf{m})$ .

On entry,  $\mathbf{pda} = \langle \text{value} \rangle$  and  $\mathbf{n} = \langle \text{value} \rangle$ .

Constraint:  $\mathbf{pda} \geq \max(1, \mathbf{n})$ .

**NE\_INTERNAL\_ERROR**

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

**7 Accuracy**

The computed matrix  $Q$  differs from an exactly orthogonal matrix by a matrix  $E$  such that

$$\|E\|_2 = O(\epsilon),$$

where  $\epsilon$  is the *machine precision*.

**8 Parallelism and Performance**

nag\_dorglq (f08ajc) is not threaded by NAG in any implementation.

nag\_dorglq (f08ajc) makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Please consult the Users' Note for your implementation for any additional implementation-specific information.

**9 Further Comments**

The total number of floating-point operations is approximately  $4mnk - 2(m + n)k^2 + \frac{4}{3}k^3$ ; when  $m = k$ , the number is approximately  $\frac{2}{3}m^2(3n - m)$ .

The complex analogue of this function is nag\_zunglq (f08awc).

**10 Example**

This example forms the leading 4 rows of the orthogonal matrix  $Q$  from the  $LQ$  factorization of the matrix  $A$ , where

$$A = \begin{pmatrix} -5.42 & 3.28 & -3.68 & 0.27 & 2.06 & 0.46 \\ -1.65 & -3.40 & -3.20 & -1.03 & -4.06 & -0.01 \\ -0.37 & 2.35 & 1.90 & 4.31 & -1.76 & 1.13 \\ -3.15 & -0.11 & 1.99 & -2.70 & 0.26 & 4.50 \end{pmatrix}.$$

The rows of  $Q$  form an orthonormal basis for the space spanned by the rows of  $A$ .

## 10.1 Program Text

```
/* nag_dorglq (f08ajc) Example Program.
*
* Copyright 2001 Numerical Algorithms Group.
*
* Mark 7, 2001.
* Mark 7b revised, 2004.
*/
#include <stdio.h>
#include <nag.h>
#include <nag_stlib.h>
#include <nagf08.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    Integer i, j, m, n, pda;
    Integer exit_status = 0;
    NagError fail;
    Nag_OrderType order;
    /* Arrays */
    char *title = 0;
    double *a = 0, *tau = 0;

#ifdef NAG_COLUMN_MAJOR
#define A(I, J) a[(J - 1) * pda + I - 1]
    order = Nag_ColMajor;
#else
#define A(I, J) a[(I - 1) * pda + J - 1]
    order = Nag_RowMajor;
#endif

INIT_FAIL(fail);

printf("nag_dorglq (f08ajc) Example Program Results\n\n");

/* Skip heading in data file */
scanf("%*[^\n] ");
scanf("%ld%ld%*[^\n] ", &m, &n);
#ifdef NAG_COLUMN_MAJOR
    pda = m;
#else
    pda = n;
#endif

/* Allocate memory */
if (!(title = NAG_ALLOC(31, char)) ||
    !(a = NAG_ALLOC(m * n, double)) ||
    !(tau = NAG_ALLOC(m, double)))
{
    printf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Read A from data file */
for (i = 1; i <= m; ++i)
{
    for (j = 1; j <= n; ++j)
        scanf("%lf", &A(i, j));
}
scanf("%*[^\n] ");

/* Compute the LQ factorization of A */
/* nag_dgelsf (f08ahc).
 * LQ factorization of real general rectangular matrix
 */
nag_dgelsf(order, m, n, a, pda, tau, &fail);
```

```

if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dgelsf (f08ahc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Form the leading M rows of Q explicitly */
/* nag_dorglq (f08ajc). */
/* Form all or part of orthogonal Q from LQ factorization
 * determined by nag_dgelsf (f08ahc)
 */
nag_dorglq(order, m, n, m, a, pda, tau, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_dorglq (f08ajc).\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}

/* Print the leading M rows of Q only */
sprintf(title, "The leading %2ld rows of Q\n", m);
/* nag_gen_real_mat_print (x04cac).
 * Print real general matrix (easy-to-use)
 */
fflush(stdout);
nag_gen_real_mat_print(order, Nag_GeneralMatrix, Nag_NonUnitDiag, m, n,
                      a, pda, title, 0, &fail);
if (fail.code != NE_NOERROR)
{
    printf("Error from nag_gen_real_mat_print (x04cac).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}

END:
NAG_FREE(title);
NAG_FREE(a);
NAG_FREE(tau);

return exit_status;
}

```

## 10.2 Program Data

```

nag_dorglq (f08ajc) Example Program Data
 4   6                                :Values of M and N
-5.42   3.28  -3.68   0.27   2.06   0.46
-1.65  -3.40  -3.20  -1.03  -4.06  -0.01
-0.37   2.35   1.90   4.31  -1.76   1.13
-3.15  -0.11   1.99  -2.70   0.26   4.50  :End of matrix A

```

## 10.3 Program Results

nag\_dorglq (f08ajc) Example Program Results

The leading 4 rows of Q

|   | 1       | 2       | 3       | 4       | 5       | 6       |
|---|---------|---------|---------|---------|---------|---------|
| 1 | -0.7104 | 0.4299  | -0.4824 | 0.0354  | 0.2700  | 0.0603  |
| 2 | -0.2412 | -0.5323 | -0.4845 | -0.1595 | -0.6311 | -0.0027 |
| 3 | 0.1287  | -0.2619 | -0.2108 | -0.7447 | 0.5227  | -0.2063 |
| 4 | -0.3403 | -0.0921 | 0.4546  | -0.3869 | -0.0465 | 0.7191  |

---