

NAG Library Routine Document

F08TSF (ZHPGST)

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F08TSF (ZHPGST) reduces a complex Hermitian-definite generalized eigenproblem $Az = \lambda Bz$, $ABz = \lambda z$ or $BAz = \lambda z$ to the standard form $Cy = \lambda y$, where A is a complex Hermitian matrix and B has been factorized by F07GRF (ZPPTRF), using packed storage.

2 Specification

SUBROUTINE F08TSF (ITYPE, UPLO, N, AP, BP, INFO)

INTEGER ITYPE, N, INFO
 COMPLEX (KIND=nag_wp) AP(*), BP(*)
 CHARACTER(1) UPLO

The routine may be called by its LAPACK name *zhpgst*.

3 Description

To reduce the complex Hermitian-definite generalized eigenproblem $Az = \lambda Bz$, $ABz = \lambda z$ or $BAz = \lambda z$ to the standard form $Cy = \lambda y$ using packed storage, F08TSF (ZHPGST) must be preceded by a call to F07GRF (ZPPTRF) which computes the Cholesky factorization of B ; B must be positive definite.

The different problem types are specified by the parameter ITYPE, as indicated in the table below. The table shows how C is computed by the routine, and also how the eigenvectors z of the original problem can be recovered from the eigenvectors of the standard form.

ITYPE	Problem	UPLO	B	C	z
1	$Az = \lambda Bz$	'U' 'L'	$U^H U$ LL^H	$U^{-H} A U^{-1}$ $L^{-1} A L^{-H}$	$U^{-1} y$ $L^{-H} y$
2	$ABz = \lambda z$	'U' 'L'	$U^H U$ LL^H	$U A U^H$ $L^H A L$	$U^{-1} y$ $L^{-H} y$
3	$BAz = \lambda z$	'U' 'L'	$U^H U$ LL^H	$U A U^H$ $L^H A L$	$U^H y$ $L y$

4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Parameters

- 1: ITYPE – INTEGER *Input*
On entry: indicates how the standard form is computed.
 ITYPE = 1
 if UPLO = 'U', $C = U^{-H}AU^{-1}$;
 if UPLO = 'L', $C = L^{-1}AL^{-H}$.
 ITYPE = 2 or 3
 if UPLO = 'U', $C = UAU^H$;
 if UPLO = 'L', $C = L^H AL$.
Constraint: ITYPE = 1, 2 or 3.
- 2: UPLO – CHARACTER(1) *Input*
On entry: indicates whether the upper or lower triangular part of A is stored and how B has been factorized.
 UPLO = 'U'
 The upper triangular part of A is stored and $B = U^H U$.
 UPLO = 'L'
 The lower triangular part of A is stored and $B = LL^H$.
Constraint: UPLO = 'U' or 'L'.
- 3: N – INTEGER *Input*
On entry: n , the order of the matrices A and B .
Constraint: $N \geq 0$.
- 4: AP(*) – COMPLEX (KIND=nag_wp) array *Input/Output*
Note: the dimension of the array AP must be at least $\max(1, N \times (N + 1)/2)$.
On entry: the upper or lower triangle of the n by n Hermitian matrix A , packed by columns.
 More precisely,
 if UPLO = 'U', the upper triangle of A must be stored with element A_{ij} in $AP(i + j(j - 1)/2)$ for $i \leq j$;
 if UPLO = 'L', the lower triangle of A must be stored with element A_{ij} in $AP(i + (2n - j)(j - 1)/2)$ for $i \geq j$.
On exit: the upper or lower triangle of AP is overwritten by the corresponding upper or lower triangle of C as specified by ITYPE and UPLO, using the same packed storage format as described above.
- 5: BP(*) – COMPLEX (KIND=nag_wp) array *Input*
Note: the dimension of the array BP must be at least $\max(1, N \times (N + 1)/2)$.
On entry: the Cholesky factor of B as specified by UPLO and returned by F07GRF (ZPPTRF).
- 6: INFO – INTEGER *Output*
On exit: INFO = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

Errors or warnings detected by the routine:

INFO < 0

If INFO = $-i$, argument i had an illegal value. An explanatory message is output, and execution of the program is terminated.

7 Accuracy

Forming the reduced matrix C is a stable procedure. However it involves implicit multiplication by B^{-1} if (ITYPE = 1) or B (if ITYPE = 2 or 3). When F08TSF (ZHPGST) is used as a step in the computation of eigenvalues and eigenvectors of the original problem, there may be a significant loss of accuracy if B is ill-conditioned with respect to inversion. See the document for F08SNF (ZHEGV) for further details.

8 Further Comments

The total number of real floating point operations is approximately $4n^3$.

The real analogue of this routine is F08TEF (DSPGST).

9 Example

This example computes all the eigenvalues of $Az = \lambda Bz$, where

$$A = \begin{pmatrix} -7.36 + 0.00i & 0.77 - 0.43i & -0.64 - 0.92i & 3.01 - 6.97i \\ 0.77 + 0.43i & 3.49 + 0.00i & 2.19 + 4.45i & 1.90 + 3.73i \\ -0.64 + 0.92i & 2.19 - 4.45i & 0.12 + 0.00i & 2.88 - 3.17i \\ 3.01 + 6.97i & 1.90 - 3.73i & 2.88 + 3.17i & -2.54 + 0.00i \end{pmatrix}$$

and

$$B = \begin{pmatrix} 3.23 + 0.00i & 1.51 - 1.92i & 1.90 + 0.84i & 0.42 + 2.50i \\ 1.51 + 1.92i & 3.58 + 0.00i & -0.23 + 1.11i & -1.18 + 1.37i \\ 1.90 - 0.84i & -0.23 - 1.11i & 4.09 + 0.00i & 2.33 - 0.14i \\ 0.42 - 2.50i & -1.18 - 1.37i & 2.33 + 0.14i & 4.29 + 0.00i \end{pmatrix},$$

using packed storage. Here B is Hermitian positive definite and must first be factorized by F07GRF (ZPPTRF). The program calls F08TSF (ZHPGST) to reduce the problem to the standard form $Cy = \lambda y$; then F08GSF (ZHPTRD) to reduce C to tridiagonal form, and F08JFF (DSTERF) to compute the eigenvalues.

9.1 Program Text

```

Program f08tsfe
!
!   F08TSF Example Program Text
!
!   Mark 24 Release. NAG Copyright 2012.
!
!   .. Use Statements ..
!   Use nag_library, Only: dsterf, nag_wp, zhpgst, zhptrd, zpptrf
!   .. Implicit None Statement ..
!   Implicit None
!   .. Parameters ..
!   Integer, Parameter          :: nin = 5, nout = 6
!   .. Local Scalars ..
!   Integer                    :: i, info, j, n
!   Character (1)              :: uplo
!   .. Local Arrays ..
!   Complex (Kind=nag_wp), Allocatable :: ap(:), bp(:), tau(:)
!   Real (Kind=nag_wp), Allocatable   :: d(:), e(:)

```

```

!      .. Executable Statements ..
      Write (nout,*) 'F08TSF Example Program Results'
!      Skip heading in data file
      Read (nin,*)
      Read (nin,*) n

      Allocate (ap(n*(n+1)/2),bp(n*(n+1)/2),tau(n),d(n),e(n-1))

!      Read A and B from data file

      Read (nin,*) uplo
      If (uplo=='U') Then
        Read (nin,*)((ap(i+j*(j-1)/2),j=i,n),i=1,n)
        Read (nin,*)((bp(i+j*(j-1)/2),j=i,n),i=1,n)
      Else If (uplo=='L') Then
        Read (nin,*)((ap(i+(2*n-j)*(j-1)/2),j=1,i),i=1,n)
        Read (nin,*)((bp(i+(2*n-j)*(j-1)/2),j=1,i),i=1,n)
      End If

!      Compute the Cholesky factorization of B
!      The NAG name equivalent of zpptrf is f07grf
      Call zpptrf(uplo,n,bp,info)

      Write (nout,*)
      If (info>0) Then
        Write (nout,*) 'B is not positive definite.'
      Else

!      Reduce the problem to standard form C*y = lambda*y, storing
!      the result in A
!      The NAG name equivalent of zhpgst is f08tsf
      Call zhpgst(1,uplo,n,ap,bp,info)

!      Reduce C to tridiagonal form T = (Q**H)*C*Q
!      The NAG name equivalent of zhptrd is f08gsf
      Call zhptrd(uplo,n,ap,d,e,tau,info)

!      Calculate the eigenvalues of T (same as C)
!      The NAG name equivalent of dsterf is f08jff
      Call dsterf(n,d,e,info)

      If (info>0) Then
        Write (nout,*) 'Failure to converge.'
      Else

!      Print eigenvalues

        Write (nout,*) 'Eigenvalues'
        Write (nout,99999) d(1:n)
      End If
    End If

99999 Format (3X,(9F8.4))
      End Program f08tsfe

```

9.2 Program Data

F08TSF Example Program Data

```

4                                     :Value of N
'L'                                   :Value of UPLO
(-7.36, 0.00)
( 0.77, 0.43) ( 3.49, 0.00)
(-0.64, 0.92) ( 2.19,-4.45) ( 0.12, 0.00)
( 3.01, 6.97) ( 1.90,-3.73) ( 2.88, 3.17) (-2.54, 0.00) :End of matrix A
( 3.23, 0.00)
( 1.51, 1.92) ( 3.58, 0.00)
( 1.90,-0.84) (-0.23,-1.11) ( 4.09, 0.00)
( 0.42,-2.50) (-1.18,-1.37) ( 2.33, 0.14) ( 4.29, 0.00) :End of matrix B

```

9.3 Program Results

F08TSF Example Program Results

Eigenvalues

-5.9990 -2.9936 0.5047 3.9990
