

NAG Library Routine Document

F11DKF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

1 Purpose

F11DKF computes the **approximate** solution of a real, symmetric or nonsymmetric, sparse system of linear equations applying a number of Jacobi iterations. It is expected that F11DKF will be used as a preconditioner for the iterative solution of real sparse systems of equations.

2 Specification

```
SUBROUTINE F11DKF (STORE, TRANS, INIT, NITER, N, NNZ, A, IROW, ICOL, CHECK,      &
                  B, X, DIAG, WORK, IFAIL)
INTEGER          NITER, N, NNZ, IROW(NNZ), ICOL(NNZ), IFAIL
REAL (KIND=nag_wp) A(NNZ), B(N), X(N), DIAG(N), WORK(N)
CHARACTER(1)     STORE, TRANS, INIT, CHECK
```

3 Description

F11DKF computes the **approximate** solution of the real sparse system of linear equations $Ax = b$ using NITER iterations of the Jacobi algorithm (see also Golub and Van Loan (1996) and Young (1971)):

$$x_{k+1} = x_k + D^{-1}(b - Ax_k) \quad (1)$$

where $k = 1, 2, \dots, \text{NITER}$ and $x_0 = 0$.

F11DKF can be used both for nonsymmetric and symmetric systems of equations. For symmetric matrices, either all nonzero elements of the matrix A can be supplied using coordinate storage (CS), or only the nonzero elements of the lower triangle of A , using symmetric coordinate storage (SCS) (see the F11 Chapter Introduction).

It is expected that F11DKF will be used as a preconditioner for the iterative solution of real sparse systems of equations, using either the suite comprising the routines F11GDF, F11GEF and F11GFF, for symmetric systems, or the suite comprising the routines F11BDF, F11BEF and F11BFF, for nonsymmetric systems of equations.

4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

Young D (1971) *Iterative Solution of Large Linear Systems* Academic Press, New York

5 Parameters

1: STORE – CHARACTER(1) *Input*

On entry: specifies whether the matrix A is stored using symmetric coordinate storage (SCS) (applicable only to a symmetric matrix A) or coordinate storage (CS) (applicable to both symmetric and nonsymmetric matrices).

STORE = 'N'

The complete matrix A is stored in CS format.

STORE = 'S'

The lower triangle of the symmetric matrix A is stored in SCS format.

Constraint: STORE = 'N' or 'S'.

2: TRANS – CHARACTER(1) *Input*

On entry: if STORE = 'N', specifies whether the approximate solution of $Ax = b$ or of $A^T x = b$ is required.

TRANS = 'N'

The approximate solution of $Ax = b$ is calculated.

TRANS = 'T'

The approximate solution of $A^T x = b$ is calculated.

Suggested value: if the matrix A is symmetric and stored in CS format, it is recommended that TRANS = 'N' for reasons of efficiency.

Constraint: TRANS = 'N' or 'T'.

3: INIT – CHARACTER(1) *Input*

On entry: on first entry, INIT should be set to 'I', unless the diagonal elements of A are already stored in the array DIAG. If DIAG already contains the diagonal of A , it must be set to 'N'.

INIT = 'N'

DIAG must contain the diagonal of A .

INIT = 'I'

DIAG will store the diagonal of A on exit.

Suggested value: INIT = 'I' on first entry; INIT = 'N', subsequently, unless DIAG has been overwritten.

Constraint: INIT = 'N' or 'I'.

4: NITER – INTEGER *Input*

On entry: the number of Jacobi iterations requested.

Constraint: NITER ≥ 1 .

5: N – INTEGER *Input*

On entry: n , the order of the matrix A .

Constraint: N ≥ 1 .

6: NNZ – INTEGER *Input*

On entry: if STORE = 'N', the number of nonzero elements in the matrix A .

If STORE = 'S', the number of nonzero elements in the lower triangle of the matrix A .

Constraints:

if STORE = 'N', $1 \leq \text{NNZ} \leq N^2$;

if STORE = 'S', $1 \leq \text{NNZ} \leq N \times (N + 1)/2$.

7: A(NNZ) – REAL (KIND=nag_wp) array *Input*

On entry: if STORE = 'N', the nonzero elements in the matrix A (CS format).

If STORE = 'S', the nonzero elements in the lower triangle of the matrix A (SCS format).

In both cases, the elements of either A or of its lower triangle must be ordered by increasing row index and by increasing column index within each row. Multiple entries for the same row and

columns indices are not permitted. The routine F11ZAF or F11ZBF may be used to reorder the elements in this way for CS and SCS storage, respectively.

- 8: IROW(NNZ) – INTEGER array *Input*
 9: ICOL(NNZ) – INTEGER array *Input*

On entry: if STORE = 'N', the row and column indices of the nonzero elements supplied in A.

If STORE = 'S', the row and column indices of the nonzero elements of the lower triangle of the matrix A supplied in A.

Constraints:

$1 \leq \text{IROW}(i) \leq N$, for $i = 1, 2, \dots, \text{NNZ}$;
 if STORE = 'N', $1 \leq \text{ICOL}(i) \leq N$, for $i = 1, 2, \dots, \text{NNZ}$;
 if STORE = 'S', $1 \leq \text{ICOL}(i) \leq \text{IROW}(i)$, for $i = 1, 2, \dots, \text{NNZ}$;
 either $\text{IROW}(i-1) < \text{IROW}(i)$ or both $\text{IROW}(i-1) = \text{IROW}(i)$ and
 $\text{ICOL}(i-1) < \text{ICOL}(i)$, for $i = 2, 3, \dots, \text{NNZ}$.

- 10: CHECK – CHARACTER(1) *Input*

On entry: specifies whether or not the CS or SCS representation of the matrix A should be checked.

CHECK = 'C'

Checks are carried out on the values of N, NNZ, IROW, ICOL; if INIT = 'N', DIAG is also checked.

CHECK = 'N'

None of these checks are carried out.

See also Section 8.2.

Constraint: CHECK = 'C' or 'N'.

- 11: B(N) – REAL (KIND=nag_wp) array *Input*

On entry: the right-hand side vector b .

- 12: X(N) – REAL (KIND=nag_wp) array *Output*

On exit: the approximate solution vector x_{NITER} .

- 13: DIAG(N) – REAL (KIND=nag_wp) array *Input/Output*

On entry: if INIT = 'N', the diagonal elements of A.

On exit: if INIT = 'N', unchanged on exit.

If INIT = 'I', the diagonal elements of A.

- 14: WORK(N) – REAL (KIND=nag_wp) array *Workspace*

- 15: IFAIL – INTEGER *Input/Output*

On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this parameter, the recommended value is 0. **When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.**

On exit: IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

6 Error Indicators and Warnings

If on entry $IFAIL = 0$ or -1 , explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

$IFAIL = 1$

On entry, $STORE \neq 'N'$ or $'S'$,
 or $TRANS \neq 'N'$ or $'T'$,
 or $INIT \neq 'N'$ or $'I'$,
 or $CHECK \neq 'C'$ or $'N'$,
 or $NITER \leq 0$.

$IFAIL = 2$

On entry, $N < 1$,
 or $NNZ < 1$,
 or $NNZ > N^2$, if $STORE = 'N'$,
 or $1 \leq NNZ \leq [N(N+1)]/2$, if $STORE = 'S'$.

$IFAIL = 3$

On entry, the arrays $IROW$ and $ICOL$ fail to satisfy the following constraints:

$$1 \leq IROW(i) \leq N \text{ and}$$

if $STORE = 'N'$ then $1 \leq ICOL(i) \leq N$, or

if $STORE = 'S'$ then $1 \leq ICOL(i) \leq IROW(i)$, for $i = 1, 2, \dots, NNZ$.

$IROW(i-1) < IROW(i)$ or $IROW(i-1) = IROW(i)$ and $ICOL(i-1) < ICOL(i)$, for $i = 2, 3, \dots, NNZ$.

Therefore a nonzero element has been supplied which does not lie within the matrix A , is out of order, or has duplicate row and column indices. Call either F11ZAF or F11ZBF to reorder and sum or remove duplicates when $STORE = 'N'$ or $STORE = 'S'$, respectively.

$IFAIL = 4$

On entry, $INIT = 'N'$ and some diagonal elements of A stored in $DIAG$ are zero.

$IFAIL = 5$

On entry, $INIT = 'I'$ and some diagonal elements of A are zero.

7 Accuracy

In general, the Jacobi method cannot be used on its own to solve systems of linear equations. The rate of convergence is bound by its spectral properties (see, for example, Golub and Van Loan (1996)) and as a solver, the Jacobi method can only be applied to a limited set of matrices. One condition that guarantees convergence is strict diagonal dominance.

However, the Jacobi method can be used successfully as a preconditioner to a wider class of systems of equations. The Jacobi method has good vector/parallel properties, hence it can be applied very efficiently. Unfortunately, it is not possible to provide criteria which define the applicability of the Jacobi method as a preconditioner, and its usefulness must be judged for each case.

8 Further Comments

8.1 Timing

The time taken for a call to F11DKF is proportional to $NITER \times NNZ$.

8.2 Use of CHECK

It is expected that a common use of F11DKF will be as preconditioner for the iterative solution of real, symmetric or nonsymmetric, linear systems. In this situation, F11DKF is likely to be called many times. In the interests of both reliability and efficiency, you are recommended to set CHECK = 'C' for the first of such calls, and to set CHECK = 'N' for all subsequent calls.

9 Example

This example solves the real sparse nonsymmetric system of equations $Ax = b$ iteratively using F11DKF as a preconditioner.

9.1 Program Text

```

Program fl1dkfe

!      F11DKF Example Program Text

!      Mark 24 Release. NAG Copyright 2012.

!      .. Use Statements ..
Use nag_library, Only: fl1bdf, fl1bef, fl1bff, fl1dkf, fl1xaf, nag_wp
!      .. Implicit None Statement ..
Implicit None
!      .. Parameters ..
Integer, Parameter          :: nin = 5, nout = 6
!      .. Local Scalars ..
Real (Kind=nag_wp)         :: anorm, sigmax, stplhs, stprhs, tol
Integer                    :: i, ifail, ifail1, irevcn, iterm,      &
                             itn, lwork, lwreq, m, maxitn, monit, &
                             n, niter, nnz
Character (1)              :: init, norm, precon, weight
Character (8)              :: method
!      .. Local Arrays ..
Real (Kind=nag_wp), Allocatable :: a(:), b(:), diag(:), wgt(:),      &
                             work(:), x(:)
Integer, Allocatable        :: icol(:), irow(:)
!      .. Executable Statements ..
Write (nout,*) 'F11DKF Example Program Results'

!      Skip heading in data file

Read (nin,*)
Read (nin,*) n
Read (nin,*) nnz
lwork = 200
Allocate (a(nnz),b(n),diag(n),wgt(n),work(lwork),x(n),icol(nnz), &
         irow(nnz))

!      Read or initialize the parameters for the iterative solver

Read (nin,*) method
Read (nin,*) precon, norm, weight, iterm
Read (nin,*) m, tol, maxitn
Read (nin,*) monit
anorm = 0.0E0_nag_wp
sigmax = 0.0E0_nag_wp

!      Read the parameters for the preconditioner

Read (nin,*) niter

!      Read the non-zero elements of the matrix A

Do i = 1, nnz
  Read (nin,*) a(i), irow(i), icol(i)
End Do

```

```

!      Read right-hand side vector b and initial approximate solution

      Read (nin,*) b(1:n)
      Read (nin,*) x(1:n)

!      Call F11BDF to initialize the solver

!      ifail: behaviour on error exit
!              =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
      ifail = 0
      Call f11bdf(method,precon,norm,weight,iterm,n,m,tol,maxitn,anorm,sigmax, &
        monit,lwreq,work,lwork,ifail)

!      Call repeatedly F11BEF to solve the equations
!      Note that the arrays B and X are overwritten

!      On final exit, X will contain the solution and B the residual
!      vector

      irevcm = 0
      init = 'I'

      ifail = 1
loop: Do
      Call f11bef(irevcm,x,b,wgt,work,lwreq,ifail)

      If (irevcm/=4) Then
        ifail1 = -1
        Select Case (irevcm)
          Case (-1)

            Call f11xaf('Transpose',n,nnz,a,irow,icol,'No checking',x,b, &
              ifail1)

          Case (1)

            Call f11xaf('No transpose',n,nnz,a,irow,icol,'No checking',x,b, &
              ifail1)

          Case (2)

            Call f11dkf('Non symmetric','N',init,niter,n,nnz,a,irow,icol, &
              'Check',x,b,diag,work(lwreq+1),ifail1)

            init = 'N'
          Case (3)

            ifail1 = 0
            Call f11bff(itn,stplhs,stprhs,anorm,sigmax,work,lwreq,ifail1)

            Write (nout,99999) itn, stplhs
          End Select
          If (ifail1/=0) irevcm = 6
          Else If (ifail/=0) Then
            Write (nout,99993) ifail
            Go To 100
          Else
            Exit loop
          End If
        End Do loop

!      Obtain information about the computation

      ifail1 = 0
      Call f11bff(itn,stplhs,stprhs,anorm,sigmax,work,lwreq,ifail1)

!      Print the output data
      Write (nout,99996)
      Write (nout,99995) 'Number of iterations for convergence: ', itn
      Write (nout,99994) 'Residual norm: ', stplhs
      Write (nout,99994) 'Right-hand side of termination criterion:', stprhs

```

```

      Write (nout,99994) '1-norm of matrix A:                ', anorm
!      Output x
      Write (nout,99998)
      Write (nout,99997)(x(i),b(i),i=1,n)
100   Continue

99999 Format (/1X,'Monitoring at iteration no.',I4/1X,1P,'residual no','rm: ', &
      E14.4)
99998 Format (/2X,' Solution vector',2X,' Residual vector')
99997 Format (1X,1P,E16.4,1X,E16.4)
99996 Format (/1X,'Final Results')
99995 Format (1X,A,I4)
99994 Format (1X,A,1P,E14.4)
99993 Format (1X/1X,' ** F11BEF returned with IFAIL = ',I5)
      End Program fl1dkfe

```

9.2 Program Data

F11DKF Example Program Data

```

      8          N
     24         NNZ
      'BICGSTAB' METHOD
      'P' '1' 'N' 1 PRECON, NORM, WEIGHT, ITERM
      2 1.0D-6 20 M, TOL, MAXITN
      1         MONIT
      4         NITER
      4. 1 1
     -1. 1 4
      1. 1 8
      4. 2 1
     -5. 2 2
      2. 2 5
     -7. 3 3
      2. 3 6
      2. 4 1
     -1. 4 3
      6. 4 4
      2. 4 7
     -1. 5 2
      8. 5 5
     -2. 5 7
     -2. 6 1
      5. 6 3
      8. 6 6
     -2. 7 3
     -1. 7 5
      7. 7 7
     -1. 8 2
      2. 8 6
      6. 8 8      A(I), IROW(I), ICOL(I), I=1,...,NNZ
      6. 8. -9. 46.
     17. 21. 22. 34. B(I), I=1,...,N
      0. 0. 0. 0.
      0. 0. 0. 0. X(I), I=1,...,N

```

9.3 Program Results

F11DKF Example Program Results

Final Results

```

Number of iterations for convergence:      2
Residual norm:                            1.1177E-04
Right-hand side of termination criterion:  5.4082E-04
1-norm of matrix A:                       1.5000E+01

```

```

Solution vector      Residual vector
 1.7035E+00          3.2377E-07
 1.0805E+00          -1.7625E-05

```

1.8305E+00	2.7964E-05
6.0251E+00	-2.5914E-05
3.2942E+00	7.8156E-06
1.9068E+00	9.2064E-06
4.1365E+00	-3.0848E-06
5.2111E+00	1.9834E-05
