

NAG Library Function Document

nag_jacobian_elliptic (s21cbc)

1 Purpose

nag_jacobian_elliptic (s21cbc) evaluates the Jacobian elliptic functions $\operatorname{sn} z$, $\operatorname{cn} z$ and $\operatorname{dn} z$ for a complex argument z .

2 Specification

```
#include <nag.h>
#include <nags.h>

void nag_jacobian_elliptic (Complex z, double ak2, Complex *sn, Complex *cn,
    Complex *dn, NagError *fail)
```

3 Description

nag_jacobian_elliptic (s21cbc) evaluates the Jacobian elliptic functions $\operatorname{sn}(z | k)$, $\operatorname{cn}(z | k)$ and $\operatorname{dn}(z | k)$ given by

$$\begin{aligned}\operatorname{sn}(z | k) &= \sin \phi \\ \operatorname{cn}(z | k) &= \cos \phi \\ \operatorname{dn}(z | k) &= \sqrt{1 - k^2 \sin^2 \phi},\end{aligned}$$

where z is a complex argument, k is a real argument (the *modulus*) with $k^2 \leq 1$ and ϕ (the *amplitude* of z) is defined by the integral

$$z = \int_0^\phi \frac{d\theta}{\sqrt{1 - k^2 \sin^2 \theta}}.$$

The above definitions can be extended for values of $k^2 > 1$ (see Salzer (1962)) by means of the formulae

$$\begin{aligned}\operatorname{sn}(z | k) &= k_1 \operatorname{sn}(kz | k_1) \\ \operatorname{cn}(z | k) &= \operatorname{dn}(kz | k_1) \\ \operatorname{dn}(z | k) &= \operatorname{cn}(kz | k_1),\end{aligned}$$

where $k_1 = 1/k$.

Special values include

$$\begin{aligned}\operatorname{sn}(z | 0) &= \sin z \\ \operatorname{cn}(z | 0) &= \cos z \\ \operatorname{dn}(z | 0) &= 1 \\ \operatorname{sn}(z | 1) &= \tanh z \\ \operatorname{cn}(z | 1) &= \operatorname{sech} z \\ \operatorname{dn}(z | 1) &= \operatorname{sech} z.\end{aligned}$$

These functions are often simply written as $\operatorname{sn} z$, $\operatorname{cn} z$ and $\operatorname{dn} z$, thereby avoiding explicit reference to the argument k . They can also be expressed in terms of Jacobian theta functions (see nag_jacobian_theta (s21ccc)).

Another nine elliptic functions may be computed via the formulae

$$\begin{aligned}
 \operatorname{cd} z &= \operatorname{cn} z / \operatorname{dn} z \\
 \operatorname{sd} z &= \operatorname{sn} z / \operatorname{dn} z \\
 \operatorname{nd} z &= 1 / \operatorname{dn} z \\
 \operatorname{dc} z &= \operatorname{dn} z / \operatorname{cn} z \\
 \operatorname{nc} z &= 1 / \operatorname{cn} z \\
 \operatorname{sc} z &= \operatorname{sn} z / \operatorname{cn} z \\
 \operatorname{ns} z &= 1 / \operatorname{sn} z \\
 \operatorname{ds} z &= \operatorname{dn} z / \operatorname{sn} z \\
 \operatorname{cs} z &= \operatorname{cn} z / \operatorname{sn} z
 \end{aligned}$$

(see Abramowitz and Stegun (1972)).

The values of $\operatorname{sn} z$, $\operatorname{cn} z$ and $\operatorname{dn} z$ are obtained by calls to `nag_real_jacobian_elliptic` (s21cac). Further details can be found in Section 9.

4 References

Abramowitz M and Stegun I A (1972) *Handbook of Mathematical Functions* (3rd Edition) Dover Publications

Salzer H E (1962) Quick calculation of Jacobian elliptic functions *Comm. ACM* **5** 399

5 Arguments

- | | | |
|----|---|---------------------|
| 1: | z – Complex | <i>Input</i> |
| | <i>On entry:</i> the argument z of the functions. | |
| | <i>Constraints:</i> | |
| | $\operatorname{abs}(z.re) \leq \sqrt{\lambda}$; | |
| | $\operatorname{abs}(z.im) \leq \sqrt{\lambda}$, where $\lambda = 1/\operatorname{nag_real_safe_small_number}$. | |
| 2: | ak2 – double | <i>Input</i> |
| | <i>On entry:</i> the value of k^2 . | |
| | <i>Constraint:</i> $0.0 \leq \mathbf{ak2} \leq 1.0$. | |
| 3: | sn – Complex * | <i>Output</i> |
| 4: | cn – Complex * | <i>Output</i> |
| 5: | dn – Complex * | <i>Output</i> |
| | <i>On exit:</i> the values of the functions $\operatorname{sn} z$, $\operatorname{cn} z$ and $\operatorname{dn} z$, respectively. | |
| 6: | fail – NagError * | <i>Input/Output</i> |
| | The NAG error argument (see Section 3.6 in the Essential Introduction). | |

6 Error Indicators and Warnings

NE_ALLOC_FAIL

Dynamic memory allocation failed.

See Section 3.2.1.2 in the Essential Introduction for further information.

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_COMPLEX

On entry, $|z.im|$ is too large: $|z.im| = \langle value \rangle$. It must be less than $\langle value \rangle$.

On entry, $|z.re|$ is too large: $|z.re| = \langle value \rangle$. It must be less than $\langle value \rangle$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please contact NAG for assistance.

An unexpected error has been triggered by this function. Please contact NAG.
See Section 3.6.6 in the Essential Introduction for further information.

NE_NO_LICENCE

Your licence key may have expired or may not have been installed correctly.
See Section 3.6.5 in the Essential Introduction for further information.

NE_REAL

On entry, $ak2 = \langle value \rangle$.
Constraint: $ak2 \leq 1.0$.

On entry, $ak2 = \langle value \rangle$.
Constraint: $ak2 \geq 0.0$.

7 Accuracy

In principle the function is capable of achieving full relative precision in the computed values. However, the accuracy obtainable in practice depends on the accuracy of the standard elementary functions such as SIN and COS.

8 Parallelism and Performance

Not applicable.

9 Further Comments

The values of $\operatorname{sn} z$, $\operatorname{cn} z$ and $\operatorname{dn} z$ are computed via the formulae

$$\operatorname{sn} z = \frac{\operatorname{sn}(u, k) \operatorname{dn}(v, k')}{1 - \operatorname{dn}^2(u, k) \operatorname{sn}^2(v, k')} + i \frac{\operatorname{cn}(u, k) \operatorname{dn}(u, k) \operatorname{sn}(v, k') \operatorname{cn}(v, k')}{1 - \operatorname{dn}^2(u, k) \operatorname{sn}^2(v, k')}$$

$$\operatorname{cn} z = \frac{\operatorname{cn}(u, k) \operatorname{cn}(v, k')}{1 - \operatorname{dn}^2(u, k) \operatorname{sn}^2(v, k')} - i \frac{\operatorname{sn}(u, k) \operatorname{dn}(u, k) \operatorname{sn}(v, k') \operatorname{dn}(v, k')}{1 - \operatorname{dn}^2(u, k) \operatorname{sn}^2(v, k')}$$

$$\operatorname{dn} z = \frac{\operatorname{dn}(u, k) \operatorname{cn}(v, k') \operatorname{dn}(v, k')}{1 - \operatorname{dn}^2(u, k) \operatorname{sn}^2(v, k')} - i \frac{k^2 \operatorname{sn}(u, k) \operatorname{cn}(u, k) \operatorname{sn}(v, k')}{1 - \operatorname{dn}^2(u, k) \operatorname{sn}^2(v, k')}$$

where $z = u + iv$ and $k' = \sqrt{1 - k^2}$ (the *complementary modulus*).

10 Example

This example evaluates $\operatorname{sn} z$, $\operatorname{cn} z$ and $\operatorname{dn} z$ at $z = -2.0 + 3.0i$ when $k = 0.5$, and prints the results.

10.1 Program Text

```

/* nag_jacobian_elliptic (s21cbc) Example Program.
 *
 * Copyright 2014 Numerical Algorithms Group.
 *
 * NAG C Library
 *
 * Mark 6, 2000.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nags.h>

int main(void)
{
    Complex  cn, dn, sn, z;
    Integer  exit_status = 0;
    NagError fail;
    double   ak2;

    INIT_FAIL(fail);

    /* Skip heading in data file */
#ifdef _WIN32
    scanf_s("%*[\n] ");
#else
    scanf("%*[\n] ");
#endif
    printf("nag_jacobian_elliptic (s21cbc) Example Program Results\n");
#ifdef _WIN32
    while (scanf_s(" (%lf,%lf) %lf%*[\n] ", &z.re, &z.im, &ak2) != EOF)
#else
    while (scanf(" (%lf,%lf) %lf%*[\n] ", &z.re, &z.im, &ak2) != EOF)
#endif
    {
        /* nag_jacobian_elliptic (s21cbc).
         * Jacobian elliptic functions sn, cn and dn of complex
         * argument
         */
        nag_jacobian_elliptic(z, ak2, &sn, &cn, &dn, &fail);
        printf("      z          ak2\n");
        printf(" (%8.4f,%8.4f) %10.2f\n\n", z.re, z.im, ak2);
        if (fail.code == NE_NOERROR)
        {
            printf("      sn          dn\n          cn\n\n");
            printf(" (%8.4f,%8.4f) ", sn.re, sn.im);
            printf(" (%8.4f,%8.4f) ", cn.re, cn.im);
            printf(" (%8.4f,%8.4f)", dn.re, dn.im);
            printf("\n");
        }
        else
        {
            printf("Error from nag_jacobian_elliptic (s21cbc).\n%s\n",
                fail.message);
            exit_status = 1;
            goto END;
        }
    }
    END:
    return exit_status;
}

```

10.2 Program Data

nag_jacobian_elliptic (s21cbc) Example Program Data
 (-2.0, 3.0) 0.25 : Values of z and ak2

10.3 Program Results

nag_jacobian_elliptic (s21cbc) Example Program Results

	^z		^{ak2}			
(-2.0000,	3.0000)	0.25			
	^{sn}		^{cn}	^{dn}		
(-1.5865,	0.2456)	(0.3125,	1.2468)	(-0.6395,	-0.1523)
