NAG Library Routine Document

F04BEF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

1 Purpose

F04BEF computes the solution to a real system of linear equations AX = B, where A is an n by n symmetric positive definite matrix, stored in packed format, and X and B are n by r matrices. An estimate of the condition number of A and an error bound for the computed solution are also returned.

2 Specification

```
SUBROUTINE F04BEF (UPLO, N, NRHS, AP, B, LDB, RCOND, ERRBND, IFAIL)

INTEGER N, NRHS, LDB, IFAIL

REAL (KIND=nag_wp) AP(*), B(LDB,*), RCOND, ERRBND

CHARACTER(1) UPLO
```

3 Description

The Cholesky factorization is used to factor A as $A = U^TU$, if UPLO = 'U', or $A = LL^T$, if UPLO = 'L', where U is an upper triangular matrix and L is a lower triangular matrix. The factored form of A is then used to solve the system of equations AX = B.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D (1999) *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia http://www.netlib.org/lapack/lug

Higham N J (2002) Accuracy and Stability of Numerical Algorithms (2nd Edition) SIAM, Philadelphia

5 Parameters

1: UPLO – CHARACTER(1)

Input

On entry: if UPLO = 'U', the upper triangle of the matrix A is stored.

If UPLO = 'L', the lower triangle of the matrix A is stored.

Constraint: UPLO = 'U' or 'L'.

2: N – INTEGER

Input

On entry: the number of linear equations n, i.e., the order of the matrix A.

Constraint: $N \ge 0$.

3: NRHS - INTEGER

Input

On entry: the number of right-hand sides r, i.e., the number of columns of the matrix B.

Constraint: NRHS > 0.

Mark 25 F04BEF.1

F04BEF NAG Library Manual

4: AP(*) - REAL (KIND=nag wp) array

Input/Output

Note: the dimension of the array AP must be at least $max(1, N \times (N+1)/2)$.

On entry: the n by n symmetric matrix A. The upper or lower triangular part of the symmetric matrix is packed column-wise in a linear array. The jth column of A is stored in the array AP as follows:

More precisely,

if UPLO = 'U', the upper triangle of A must be stored with element A_{ij} in AP(i+j(j-1)/2) for $i \le j$;

if UPLO = 'L', the lower triangle of A must be stored with element A_{ij} in AP(i + (2n - j)(j - 1)/2) for $i \ge j$.

On exit: if IFAIL = 0 or N + 1, the factor U or L from the Cholesky factorization $A = U^{T}U$ or $A = LL^{T}$, in the same storage format as A.

5: B(LDB,*) - REAL (KIND=nag_wp) array

Input/Output

Note: the second dimension of the array B must be at least max(1, NRHS).

On entry: the n by r matrix of right-hand sides B.

On exit: if IFAIL = 0 or N + 1, the n by r solution matrix X.

6: LDB – INTEGER

Input

On entry: the first dimension of the array B as declared in the (sub)program from which F04BEF is called.

Constraint: LDB $\geq \max(1, N)$.

7: RCOND - REAL (KIND=nag wp)

Output

On exit: if IFAIL = 0 or N + 1, an estimate of the reciprocal of the condition number of the matrix A, computed as $RCOND = 1/(\|A\|_1 \|A^{-1}\|_1)$.

8: ERRBND – REAL (KIND=nag_wp)

Output

On exit: if IFAIL = 0 or N + 1, an estimate of the forward error bound for a computed solution \hat{x} , such that $\|\hat{x} - x\|_1 / \|x\|_1 \le \text{ERRBND}$, where \hat{x} is a column of the computed solution returned in the array B and x is the corresponding column of the exact solution X. If RCOND is less than **machine precision**, then ERRBND is returned as unity.

9: IFAIL – INTEGER

Input/Output

On entry: IFAIL must be set to 0, -1 or 1. If you are unfamiliar with this parameter you should refer to Section 3.3 in the Essential Introduction for details.

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, if you are not familiar with this parameter, the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

On exit: IFAIL = 0 unless the routine detects an error or a warning has been flagged (see Section 6).

F04BEF.2 Mark 25

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

IFAIL < 0 and IFAIL $\neq -999$

If IFAIL = -i, the *i*th argument had an illegal value.

IFAIL > 0 and IFAIL $\le N$

If IFAIL = i, the leading minor of order i of A is not positive definite. The factorization could not be completed, and the solution has not been computed.

IFAIL = N + 1

RCOND is less than *machine precision*, so that the matrix A is numerically singular. A solution to the equations AX = B has nevertheless been computed.

IFAIL = -99

An unexpected error has been triggered by this routine. Please contact NAG.

See Section 3.8 in the Essential Introduction for further information.

IFAIL = -399

Your licence key may have expired or may not have been installed correctly.

See Section 3.7 in the Essential Introduction for further information.

IFAIL = -999

Dynamic memory allocation failed.

See Section 3.6 in the Essential Introduction for further information.

7 Accuracy

The computed solution for a single right-hand side, \hat{x} , satisfies an equation of the form

$$(A+E)\hat{x} = b,$$

where

$$||E||_1 = O(\epsilon)||A||_1$$

and ϵ is the *machine precision*. An approximate error bound for the computed solution is given by

$$\frac{\|\hat{x} - x\|_1}{\|x\|_1} \le \kappa(A) \frac{\|E\|_1}{\|A\|_1},$$

where $\kappa(A) = \|A^{-1}\|_1 \|A\|_1$, the condition number of A with respect to the solution of the linear equations. F04BEF uses the approximation $\|E\|_1 = \epsilon \|A\|_1$ to estimate ERRBND. See Section 4.4 of Anderson *et al.* (1999) for further details.

8 Parallelism and Performance

F04BEF is threaded by NAG for parallel execution in multithreaded implementations of the NAG Library.

F04BEF makes calls to BLAS and/or LAPACK routines, which may be threaded within the vendor library used by this implementation. Consult the documentation for the vendor library for further information.

Mark 25 F04BEF.3

F04BEF NAG Library Manual

Please consult the X06 Chapter Introduction for information on how to control and interrogate the OpenMP environment used within this routine. Please also consult the Users' Note for your implementation for any additional implementation-specific information.

9 Further Comments

The integer allocatable memory required is N, and the real allocatable memory required is $3 \times N$. Allocation failed before the solution could be computed.

The packed storage scheme is illustrated by the following example when n = 4 and UPLO = 'U'. Two-dimensional storage of the symmetric matrix A:

Packed storage of the upper triangle of A:

$$AP = \begin{bmatrix} a_{11}, & a_{12}, & a_{22}, & a_{13}, & a_{23}, & a_{33}, & a_{14}, & a_{24}, & a_{34}, & a_{44} \end{bmatrix}$$

The total number of floating-point operations required to solve the equations AX = B is proportional to $\left(\frac{1}{3}n^3 + n^2r\right)$. The condition number estimation typically requires between four and five solves and never more than eleven solves, following the factorization.

In practice the condition number estimator is very reliable, but it can underestimate the true condition number; see Section 15.3 of Higham (2002) for further details.

The complex analogue of F04BEF is F04CEF.

10 Example

This example solves the equations

$$AX = B$$
,

where A is the symmetric positive definite matrix

$$A = \begin{pmatrix} 4.16 & -3.12 & 0.56 & -0.10 \\ -3.12 & 5.03 & -0.83 & 1.18 \\ 0.56 & -0.83 & 0.76 & 0.34 \\ -0.10 & 1.18 & 0.34 & 1.18 \end{pmatrix} \quad \text{and} \quad B = \begin{pmatrix} 8.70 & 8.30 \\ -13.35 & 2.13 \\ 1.89 & 1.61 \\ -4.14 & 5.00 \end{pmatrix}.$$

An estimate of the condition number of A and an approximate error bound for the computed solutions are also printed.

10.1 Program Text

```
Program f04befe
1
     FO4BEF Example Program Text
1
     Mark 25 Release. NAG Copyright 2014.
!
     .. Use Statements ..
     Use nag_library, Only: f04bef, nag_wp, x04caf
!
     .. Implicit None Statement ..
     Implicit None
     .. Parameters ..
     1
     .. Local Scalars ..
                                 :: errbnd, rcond
     Real (Kind=nag_wp)
                                  :: i, ierr, ifail, j, ldb, n, nrhs
     Integer
!
     .. Local Arrays ..
     Real (Kind=nag_wp), Allocatable :: ap(:), b(:,:)
```

F04BEF.4 Mark 25

```
.. Executable Statements ..
      Write (nout,*) 'FO4BEF Example Program Results'
      Write (nout,*)
      Flush (nout)
      Skip heading in data file
      Read (nin,*)
      Read (nin,*) n, nrhs
      ldb = n
      Allocate (ap((n*(n+1))/2),b(ldb,nrhs))
     Read the upper or lower triangular part of the matrix A from
1
     data file
      If (uplo=='U') Then
       Read (nin,*)((ap(i+(j*(j-1))/2),j=i,n),i=1,n)
      Else If (uplo=='L') Then
        Read (nin,*)((ap(i+((2*n-j)*(j-1))/2),j=1,i),i=1,n)
      End If
!
      Read B from data file
      Read (nin,*)(b(i,1:nrhs),i=1,n)
1
      Solve the equations AX = B for X
!
      ifail: behaviour on error exit
             =0 for hard exit, =1 for quiet-soft, =-1 for noisy-soft
      ifail = 1
      Call f04bef(uplo,n,nrhs,ap,b,ldb,rcond,errbnd,ifail)
      If (ifail==0) Then
!
        Print solution, estimate of condition number and approximate
        error bound
        ierr = 0
        Call x04caf('General',' ',n,nrhs,b,ldb,'Solution',ierr)
        Write (nout,*)
        Write (nout,*) 'Estimate of condition number'
        Write (nout,99999) 1.0E0_nag_wp/rcond
        Write (nout,*)
        Write (nout,*) 'Estimate of error bound for computed solutions'
        Write (nout, 99999) errbnd
      Else If (ifail==n+1) Then
        Matrix A is numerically singular. Print estimate of
        reciprocal of condition number and solution
        Write (nout,*)
        Write (nout,*) 'Estimate of reciprocal of condition number'
        Write (nout,99999) rcond
        Write (nout,*)
        Flush (nout)
        ierr = 0
        Call x04caf('General',' ',n,nrhs,b,ldb,'Solution',ierr)
      Else If (ifail>0 .And. ifail<=n) Then</pre>
        The matrix A is not positive definite to working precision Write (nout,99998) 'The leading minor of order ', ifail, &
           ' is not positive definite'
        Write (nout, 99997) ifail
      End If
99999 Format (6X,1P,E9.1)
99998 Format (1X,A,I3,A)
99997 Format (1X, ' ** FO4BEF returned with IFAIL = ', I5)
   End Program f04befe
```

Mark 25 F04BEF.5

F04BEF NAG Library Manual

10.2 Program Data

FO4BEF Example Program Data

10.3 Program Results

FO4BEF Example Program Results

Solution

Estimate of condition number 9.7E+01

Estimate of error bound for computed solutions 1.1E-14

F04BEF.6 (last) Mark 25