

# NAG Library Routine Document

## F06GUF (ZGTHR)

**Note:** before using this routine, please read the Users' Note for your implementation to check the interpretation of *bold italicised* terms and other implementation-dependent details.

### 1 Purpose

F06GUF (ZGTHR) gathers specified (usually nonzero) elements of a complex vector  $y$  in full storage form into a sparse complex vector  $x$  in compressed form.

### 2 Specification

```
SUBROUTINE F06GUF (NZ, Y, X, INDX)
  INTEGER          NZ, INDX(*)
  COMPLEX (KIND=nag_wp) Y(*), X(*)
```

The routine may be called by its BLAS name *zgthr*.

### 3 Description

None.

### 4 References

Dodson D S, Grimes R G and Lewis J G (1991) Sparse extensions to the Fortran basic linear algebra subprograms *ACM Trans. Math. Software* **17** 253–263

### 5 Parameters

- |    |                                                                                                |               |
|----|------------------------------------------------------------------------------------------------|---------------|
| 1: | NZ – INTEGER                                                                                   | <i>Input</i>  |
|    | <i>On entry:</i> the number of nonzeros in the sparse vector $x$ .                             |               |
| 2: | Y(*) – COMPLEX (KIND=nag_wp) array                                                             | <i>Input</i>  |
|    | <b>Note:</b> the dimension of the array Y must be at least $\max_k \{\text{INDX}(k)\}$ .       |               |
|    | <i>On entry:</i> the vector $y$ . Only elements corresponding to indices in INDX are accessed. |               |
| 3: | X(*) – COMPLEX (KIND=nag_wp) array                                                             | <i>Output</i> |
|    | <b>Note:</b> the dimension of the array X must be at least $\max(1, \text{NZ})$ .              |               |
|    | <i>On exit:</i> the compressed vector $x$ .                                                    |               |
| 4: | INDX(*) – INTEGER array                                                                        | <i>Input</i>  |
|    | <b>Note:</b> the dimension of the array INDX must be at least $\max(1, \text{NZ})$ .           |               |
|    | <i>On entry:</i> INDX must contain the set of indices $J$ .                                    |               |

### 6 Error Indicators and Warnings

None.

**7 Accuracy**

Not applicable.

**8 Parallelism and Performance**

Not applicable.

**9 Further Comments**

None.

**10 Example**

None.

---